




Green Pin® Wire Rope Clip



Wire rope clip generally to EN 13411-5 Type B

Scan for
additional
product
details




- **Material:** bridge: drop forged high tensile steel SAE 1045
U-bolt: SAE 1015
- **Standard:** EN 13411-5 Type B
formerly U.S. Federal Specification FF-C-450D
- **Finish:** hot dipped galvanized
U-bolt and/or nuts for diameter bow 5, 6, 8 and 10 are electro-galvanized
- **Certification:** 2.1 2.2 CE IIB
- **Article code:** scan QR code to see article codes



G-6240



diameter wire rope	diameter	length bow	width inside	length thread	length base	thickness base	height base	weight per 100 pcs
mm	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
3 - 4	5	24	12	11	24	21	10	3
5	6	31	15	13	29	24	13	7
6 - 7	8	34	19	13	37	30	18	8.40
8	10	45	22	19	43	33	19	12.4
9 - 10	11	49	26	19	49	42	25	21
11	12	60	30	25	58	46	26	33.2
12 - 13	13	61	30	25	58	48	31	33.1
14 - 15	14	72	33	32	63	52	31	45.6
16	14	74	33	32	64	54	36	45.8
18 - 20	16	86	38	37	72	57	38	64.3
22	19	98	45	41	80	62	40	96.4
24 - 26	19	108	48	46	88	67	47	115
28 - 30	19	117	51	51	91	73	48	127
32 - 34	22	130	59	54	105	79	56	197
36	22	140	60	59	108	79	58	206
38 - 40	22	147	66	60	112	85	64	254
41 - 42	25	161	70	67	121	92	67	322
44 - 46	29	174	78	70	134	97	76	418
48 - 52	32	195	86	78	150	113	85	602
56 - 58	32	213	98	81	162	116	100	776
62 - 65	32	227	105	87	168	119	113	862
68 - 72	32	243	112	91	174	127	124	1015
75 - 78	38	271	121	98	194	135	136	1272



E-6260



Wire Rope Clip

Generally to EN 13411-5 Type A

- **Material:** bridge: malleable steel
U-bolt: mild steel
- **Standard:** EN 13411-5 Type A
formerly DIN 1142
- **Finish:** electro-galvanized
- **Certification:** 2.1 CE II B

diameter wire rope	diameter	length bow	width inside	length thread	length base	thickness base	height base	weight per 100 pcs
mm	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
5	5	25	12	14	25	13	13	2.30
6.5	6	32	14	17	30	16	14	3.90
8	8	41	18	20	39	20	18	8.40
10	8	46	20	24	40	20	21	8.40
12	10	56	24	28	50	25	24	17
13	12	64	29	29	55	28	29	26.1
14	12	66	28	31	59	30	28	28.6
16	14	76	34	35	64	32	35	42
19	14	83	37	36	68	33	40	49
22	16	96	41	40	74	34	44	67
26	20	111	46	50	84	38	51	111
30	20	127	54	55	95	41	59	140
34	22	141	60	60	105	45	67	202
40	24	159	68	65	117	49	77	268

C



Wire Rope Clip

Generally to DIN 741

- **Material:** bridge: cast
U-bolt: mild steel
- **Standard:** formerly DIN 741
- **Finish:** electro-galvanized
- **Certification:** 2.1 CE II B



E-6220



diameter wire rope	diameter	length bow	width inside	length thread	length base	thickness base	height base	weight per 100 pcs
mm	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
3	4	20	9	12	21	10	10	1
5	5	24	11	13	23	11	10	1.40
6	5	28	13	15	26	12	11	1.60
8	6	34	16	19	30	14	15	3.30
10	8	42	19	22	34	18	17	6
11	8	44	20	22	36	19	18	7
13	10	55	24	30	42	23	21	11.8
14	10	57	25	30	44	23	22	12.4
16	12	63	29	33	50	26	26	19
19	12	75	32	38	54	29	30	23.6
22	14	85	37	44	61	33	34	36.6
26	14	95	41	45	65	35	37	41
30	16	110	48	50	74	37	43	62
34	16	120	52	55	80	42	50	74.4
40	16	140	58	60	88	45	55	108
45	18	163	65	75	97	49	60	134
50	20	170	72	77	106	51	65	174