





UMS



Green Pin® Master Link GR10

Grade 10 master link

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M and ASME B30.9
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC[®] MPI[®] CE IIB
- **Article code:** scan QR code to see article codes

Scan for additional product details



diameter	chain size Tycan® chain 1 leg	chain size Tycan® chain 2 legs		working load limit	length inside	width inside	thickness	weight each
a mm	mm	$\beta \leq 45^\circ$ mm	$45^\circ < \beta \leq 60^\circ$ mm	t	b mm	c mm	d mm	kg
18	11x15	11x15	11x15	5.4	135	75	9	0.84
22	11x20 / 15x25	11x20 / 15x25	11x20 / 15x25	8.2	170	90	11	1.60
25	13x30	13x30	13x30	11.2	190	103	14	2.17
30	15x40	15x40	15x40	16	235	125	17	4

CAD





Green Pin® Master Link Assembly GR10

Grade 10 master link assembly



UMTS





- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M and ASME B30.9
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC[®] MPI[®] CE IIB
- **Article code:** scan QR code to see article codes

diameter	chain size Tycan® chain 3/4 legs		working load limit	length inside	width inside	diameter	length inside	width inside	thickness	weight each
a mm	$\beta \leq 45^\circ$ mm	$45^\circ < \beta \leq 60^\circ$ mm	t	b mm	c mm	d mm	e mm	f mm	g mm	kg
22	11x15	11x15	6.8	170	90	18	135	75	9	3.30
28	11x20 / 15x25	11x20 / 15x25	11	209	120	20	150	82	11	5.40
36	13x30	13x30	17.7	270	145	25	190	103	14	11.2
38	15x40	15x40	21.2	250	150	30	235	125	17	15.1

CAD



UMSW



Green Pin® Wider Master Link GR10

Grade 10 wider master link

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 5 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M and ASME B30.9
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC[®] MPI[®] CE IIB
- **Article code:** scan QR code to see article codes

Scan for additional product details



diameter	chain size Tycan® chain 1 leg	chain size Tycan® chain 2 legs		working load limit	length inside	width inside	thickness	weight each
a mm	mm	$\beta \leq 45^\circ$ mm	$45^\circ < \beta \leq 60^\circ$ mm	t	b mm	c mm	d mm	kg
17	11x15	11x15	11x15	4.1	160	90	9	0.85
19	11x20	11x20	11x20	6.7	160	90	9	1.08
25	15x25 / 13x30	15x25 / 13x30	15x25 / 13x30	11.5	210	115	13	2.43
33	15x40	15x40	15x40	17	270	140	17	5.40

CAD



Green Pin® Wider Master Link Assembly GR10

Grade 10 wider master link assembly

Scan for additional product details



UMTSW





- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 5 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M and ASME B30.9
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC[®] MPI[®] CE IIB
- **Article code:** scan QR code to see article codes

diameter	chain size Tycan® chain 3/4 legs		working load limit	length inside	width inside	diameter	length inside	width inside	thickness	weight each
a mm	$\beta \leq 45^\circ$ mm	$45^\circ < \beta \leq 60^\circ$ mm	t	b mm	c mm	d mm	e mm	f mm	g mm	kg
19	-	11x15	4.3	160	90	14	120	70	9	1.96
23	11x20	11x20	6.7	180	100	17	160	90	9	3.50
40	15x40	15x40	28.1	300	160	33	270	140	17	19.8

CAD



UMJT



Green Pin TyCAN® Connecting Link GR10

Grade 10 connecting link


- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC[®] MPI[®] CE IIB
- **Article code:** scan QR code to see article codes

Scan for additional product details





for chain size	working load limit	diameter	width outside	width inside	length inside	length inside	diameter eye	width inside	diameter	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	kg
11x15	2.6	9	57	14	20	55	16	19	13	0.22
11x20	4	12	66	18	23	67	18	23	16	0.37
13x30	6.8	16	83	21	32	87	24	28	20	0.78
15x40	10.3	19	103	25.5	40	107.5	28	34	24	1.46

CAD



UMJ



Green Pin® Connecting Link GR10

Grade 10 connecting link

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MPI^b DGUV CE IIB
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details




for chain size	working load limit	diameter	width outside	width inside	length inside	length inside	diameter eye	width inside	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
15x25	6.8	16	83	21	32	85	24	28	0.68

CAD INFO



FCHLIFT



Green Pin Tycan® Lifting Chain

Lifting chain made from Dyneema®

- **Material:** made from 100% Dyneema®; layers of webbing in a Mobius twist with stitching on each side
- **Safety factor:** MBL equals 4 x WLL
- **Temperature range:** -40 °C to +70 °C
- **Certification:** 2.1 2.2 MTC[®] DNV TA DNV TQ CE IIA
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details



link size	working load limit	width link	thickness link	length inside	links per meter	elongation at MBL	weight per meter	layers
mm	t	a mm	b mm	c mm		%	kg	
11x15	2.6	15	11	100	10	5	0.32	6
11x20	4	20	11	100	10	5	0.47	6
15x25	5	25	15	100	10	5	0.58	8
13x30	6.8	30	13	125	8	5	0.75	7
15x40	10.3	40	15	175	6	5	1.12	7

CAD INFO




Green Pin Tycan® Sleeve

Sleeve made from Dyneema®

- **Material:** 100% Dyneema
- **Certification:** 2.1
- **Article code:** scan QR code to see article codes



SLEEVE




for chain size	length	diameter	thickness	weight each
mm	a mm	b mm	c mm	kg
11x15	500	40	1	0.04
11x20	500	50	1	0.05
15x25	500	60	1	0.04
13x30	500	65	1	0.06
15x40	500	75	1	0.10

INFO



UCRCT



Green Pin Tycan[®] Grab Hook CL GR10

Grade 10 clevis grab hook

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL and MBL equals 2 x Lashing Capacity
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MPI^b CE IIB
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details




for chain size	working load limit	length	width	width outside	opening	thickness	width	width outside	length outside	diameter pin	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
11x15	2.6	64	17	44	15	13	23	65	109	13	0.55
11x20	4	81	22	57	20	16	29	85	138	16	1.03
15x25	5	102	24	68	25	16	40	99	178	20	2
13x30	6.8	100	32	74	30	20	40	102	177	20	1.94
15x40	10.3	128	42	96	40	24	44.7	127	216.5	24	3.37

CAD INFO



UCSO



Green Pin® Sling Hook E GR10

Grade 10 eye sling hook

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC[®] MPI[®] DGVV CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** from 10 t without flat part

Scan for
additional
product
details



for chain size	working load limit	length	diameter inside eye	width opening	thickness	width	diameter eye outside	width outside	length	width	thickness	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
11x15	2.6	103	26	30	19	24	51	87	139	12	8	0.52
11x20	4	129	36	33	24	28	65	106	171	15	10	1.09
15x25 / 13x30	6.8	152	41	37	32	39	77	133	209	18	12	1.94
15x40	10.3	191	52	43	40	43	94	165	255	21	17	3.51


CAD INFO



tycan



UCSCT



Green Pin Tyacan® Sling Hook CL GR10

Grade 10 clevis sling hook

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC[®] MPI[®] CE IIB
- **Article code:** scan QR code to see article codes



for chain size	working load limit	length	width	width opening	thickness	width	width outside	width outside	length outside	diameter pin	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
11x15	2.6	112	17	30	20	24	44	87	158	13	0.72
11x20	4	130	22	34	24	28	57	106	186	16	1.31
15x25	5	150	24	37	29	35	68	123	220	20	2.15
13x30	6.8	159	32	37	32	39	74	133	235	20	2.56
15x40	10.3	185	42	45	40	43	96	165	271	24	4.25

CAD INFO




Green Pin® Self Locking Hook E GR10

Grade 10 eye self locking hook


- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MPI^b DGUV CE IIB
- **Article code:** scan QR code to see article codes



UXLO



Scan for additional product details



for chain size	working load limit	length	diameter inside eye	width opening	thickness	width	width outside	width outside	length	width	thickness	weight each
mm	t	a	b	c	d	e	f	g	h	i	j	kg
11x15	2.6	136	30	43	24	28	57	91	178	14	8	0.91
11x20	4	168	36	48	32	34	68	110	218	16	10	1.79
15x25 / 13x30	6.8	201	47	63	37	43	87	141	264	20	13	3.36
15x40	10.3	251	60	75	43	56	111	182	332	26	16	7

CAD INFO




Green Pin® Self Locking Hook E RT GR10

Grade 10 self locking hook E RT

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MPI^b DGUV CE IIB
- **Article code:** scan QR code to see article codes



UXLORT




for chain size	working load limit	length	diameter inside eye	width opening	thickness	width	width outside	width outside	length	width	thickness	weight each
mm	t	a	b	c	d	e	f	g	h	i	j	kg
11x15	2.6	136	30	43	24	28	57	91	178	14	7	0.90
11x20	4	168	36	48	32	34	68	111	218	16	10	1.77
15x25 / 13x30	6.8	201	47	63	37	43	87	141	264	20	13	3.34
15x40	10.3	251	60	75	43	56	111	182	332	26	16	6.98

CAD INFO



UXLE



Green Pin® Self Locking Hook SE GR10

Grade 10 self locking hook with swivel

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^o MPI^o DGVV CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** equipped with thrust needle roller bearings to enable rotation under load

Scan for
additional
product
details



for chain size	working load limit	length	length inside	width inside	width opening	thickness	width	width outside	length	diameter	thickness	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
11x15	2.6	149	41	37	43	24	28	91	232	14	8	1.39
11x20	4	186	47	48	48	32	34	112	283	16	11	2.56
15x25 / 13x30	6.8	214	60	58	63	37	44	141	337	21	14	4.56
15x40	10.3	273	67	73	75	43	56	182	420	25	17	9.50

CAD INFO




Green Pin® Self Locking Hook SE RT GR10

Grade 10 swivel self locking hook with recessed trigger

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^o MPI^o DGVV CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** equipped with thrust needle roller bearings to enable rotation under load



UXLERT



for chain size	working load limit	length	length inside	width inside	width opening	thickness	width	width outside	length	diameter	thickness	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
11x15	2.6	149	41	37	43	24	28	91	232	14	8	1.38
11x20	4	186	47	48	48	32	34	112	283	16	11	2.54
15x25 / 13x30	6.8	214	60	58	63	37	44	141	337	21	14	4.54
15x40	10.3	273	67	73	75	43	56	182	420	25	17	9.48

CAD INFO


Scan for additional product details




Green Pin® ID Tag

Aluminium identification tag

- **Material:** aluminium
- **Finish:** see table below
- **Certification:** 2.1




TAG




partnumber	finish	width	length	length	weight each
		a mm	b mm	c mm	kg
TAGVIERGE	self-coloured	51	76	220	0.07
TAGJ	anodized yellow	51	76	220	0.07
TAGGREEN	anodized green	51	76	220	0.07
TAGRED	anodized red	51	76	220	0.07
TAGBLUE	anodized blue	51	76	220	0.07
TAGDEMI	self-coloured	51	38	220	0.04
TAGB without wire rope	self-coloured	51	76		0.06



TAGVIERGE



TAGJ



TAGGREEN



TAGRED



TAGBLUE



TAGDEMI




Green Pin® ID Tag for Grade 10 Slings

Forged identification tag for grade 10 slings

- **Material:** drop forged mild steel
- **Finish:** electro galvanized
- **Certification:** 2.1




UTAGF




width	length	width inside	length inside	weight each
a mm	b mm	c mm	d mm	kg
79	121	35	32	0.30

RFID



TAGRFID



Green Pin® RFID Tag

Accessory for radio-frequency identification of slings

- **Material:** stainless steel
- **Standard:** RF Protocol ISO 15693 Operating Frequency HF - 13.56 MHz with individual serial number
- **Finish:** polymer
- **Temperature range:** -40 °C up to +125 °C
- **Certification:** 21
- **Note:** IP68; water and ice proof

Scan for
additional
product
details





length	width	diameter	diameter	weight per 100 pcs
a mm	b mm	c mm	d mm	kg
53	33	12	4	1.80

RFID INFO



CHIPRFID



Green Pin® RFID Chip

Accessory for radio-frequency identification of slings

- **Material:** polymer
- **Standard:** RF Protocol ISO 15693 Operating Frequency HF - 13.56 MHz with individual serial number
- **Temperature range:** -40 °C up to +125 °C
- **Certification:** 21
- **Note:** IP68; water and ice proof

diameter	thickness	weight per 100 pcs
a mm	b mm	kg
6	2	0.02

RFID INFO



Green Pin® Self Locking Hooks GR8/GR10 Spare Kit

Replacement kit for grade 8 and 10 self locking hooks

- **Material:** steel
- **Finish:** self-coloured
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 CE IIB
- **Note:** plastic tube included, to make assembly easier

partnumber	length pin	diameter pin	width	weight each
	a mm	b mm	c mm	kg
VR1	22	6	28	0.02
VR2	26	6	31	0.03
VR3	32	8	37	0.05
VR4	40	10	47	0.10
VR5	55	10	58	0.20

partnumber	for fitting		
	UXLO	UXLC	UXLE
VR1	GPUXLO0	GPUXLC0	GPUXLE0
VR2	GPUXLO1	GPUXLC07	GPUXLE1
		GPUXLC1	
VR3	GPUXLO2	GPUXLC2	GPUXLE2
VR4	GPUXLO3	GPUXLC3	GPUXLE3
VR5	GPUXLO4	GPUXLC4	GPUXLE4
	GPUXLO5	GPUXLC5	GPUXLE5

INFO



Green Pin® Self Locking Hooks RT GR10 Spare Kit


Replacement kit for grade 8 and 10 self locking hooks with recessed trigger

- **Material:** steel
- **Finish:** self-coloured
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 CE IIB
- **Note:** plastic tube included, to make assembly easier


partnumber	length pin	diameter pin	width	weight each
	a mm	b mm	c mm	kg
GPVR2RT	26	6	31	0.03
GPVR3RT	32	8	37	0.05
GPVR4RT	40	10	47	0.10
GPVR5RT	55	10	58	0.20

partnumber	for fitting		
	UXLORT	UXLCRT	UXLERT
GPVR2RT	GPUXLO1RT	GPUXLC1RT	GPUXLE1RT
GPVR3RT	GPUXLO2RT	GPUXLC2RT	GPUXLE2RT
GPVR4RT	GPUXLO3RT	GPUXLC3RT	GPUXLE3RT
GPVR5RT	GPUXLO4RT	GPUXLC4RT	GPUXLE4RT
	GPUXLO5RT	GPUXLC5RT	GPUXLE5RT

INFO



UACT



Green Pin Tycan® Clevis Fittings GR10 Spare Kit

Grade 10 spare kit for clevis fittings

- **Material:** alloy steel, grade 10, quenched and tempered
- **Finish:** self-coloured
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 3.1 CE IIB

partnumber	diameter pin	length pin	diameter pin	length pin	weight each
	a mm	b mm	c mm	d mm	kg
GPUACT15	4	24	13	43	0.04
GPUACT20	4	24	16	56	0.08
GPUACT25	5	35	20	66	0.16
GPUACT30	5	35	20	72	0.16
GPUACT40	6	45	24	94	0.16

partnumber	for fitting	
	UCSCT	UCRCT
GPUACT15	GPUCSCT15	GPUCRCT15
GPUACT20	GPUCSCT20	GPUCRCT20
GPUACT25		GPUCRCT25
GPUACT30	GPUCSCT30	GPUCRCT30
GPUACT40	GPUCSCT40	GPUCRCT40




Green Pin Tycan® Grab Hook CL GR10 Locking Pin

Grade 10 locking pin for Green Pin Tycan® clevis grab hook

- **Material:** alloy steel, grade 10
- **Finish:** self-coloured
- **Certification:** 2.1 CE IIB



UALT



partnumber	diameter pin	length pin	weight each
	a mm	b mm	kg
GPUALT15	5.8	52	0.01
GPUALT20	5.8	63	0.02
GPUALT25	7.8	72	0.03
GPUALT30	7.8	77	0.03
GPUALT40	7.8	95	0.03


partnumber	for fitting
	UCRCT
GPUALT15	GPUCRCT15
GPUALT20	GPUCRCT20
GPUALT25	GPUCRCT25
GPUALT30	GPUCRCT30
GPUALT40	GPUCRCT40




Green Pin® Connecting Link Spare Kit GR10

Grade 10 spare kit for connecting link

- **Material:** alloy steel, grade 10, quenched and tempered
- **Finish:** self-coloured
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 3.1 CE IIB



URMJ



partnumber	diameter pin	length pin	diameter	width	weight each
	a mm	b mm	c mm	d mm	kg
GPURMJ8	6	54	13	14	0.02
GPURMJ10	8	66	16	18	0.02
GPURMJ13	10	84	22	22	0.05
GPURMJ16	12	105	25	25	0.10


partnumber	for fitting	
	UMJ	UMJT
GPURMJ8		GPUMJT15
GPURMJ10		GPUMJT20
GPURMJ13	GPUMJ13	GPUMJT30
GPURMJ16		GPUMJT40




Green Pin® Latch GR10

Forged latch for grade 10

- **Material:** steel
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 CE IIB



ULF



partnumber	width	length	diameter pin	length pin	weight each
	a mm	b mm	c mm	d mm	kg
GPULF1	31	59	5	30	0.07
GPULF2	41	65	5	40	0.11
GPULF3	41	79	6	40	0.18
GPULF4	46	81	6	45	0.20

partnumber	for fitting	
	UCSO	UCSCT
GPULF1	GPUCSO8	GPUCSCT15
GPULF2	GPUCSO10	GPUCSCT20 - GPUCSCT25
GPULF3	GPUCSO13	GPUCSCT30
GPULF4	GPUCSO16	GPUCSCT40