





UMJT



Green Pin Tyacan® Connecting Link GR10

Grade 10 connecting link

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC[®] MPI[®] CE IIB
- **Article code:** scan QR code to see article codes

Scan for additional product details



for chain size	lashing capacity	diameter	width outside	width inside	length inside	length inside	diameter eye	width inside	diameter	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	kg
13x30	13.6	16	83	21	32	87	24	28	20	0.78
15x40	20.6	19	103	25.5	40	107.5	28	34	24	1.46


CAD



Green Pin® Connecting Link GR10



Grade 10 connecting link

Scan for additional product details



- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MPI^b DGUV CE IIB
- **Article code:** scan QR code to see article codes

UMJ




for chain size	lashing capacity	diameter	width outside	width inside	length inside	length inside	diameter eye	width inside	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
15x25	13.6	16	83	21	32	85	24	28	0.68

CAD INFO



FCHLASH



Green Pin Tycan® Lashing Chain

Lashing chain made from Dyneema®

- **Material:** made from 100% Dyneema®; layers of webbing in a Mobius twist with stitching on each side
- **Safety Factor:** MBL equals 2 x Lashing Capacity
- **Temperature range:** -60 °C to +70 °C
- **Certification:** 2.1 2.2 MTC[®] DNV TQ
- **Article code:** scan QR code to see article codes

Scan for additional product details




link size	lashing capacity	width link	thickness link	length inside	links per meter	elongation at MBL	weight per meter	layers
mm	t	a mm	b mm	c mm		%	kg	
15x25	10	25	15	100	10	5	0.6	8
13x30	13.6	30	13	125	8	5	0.9	7
15x40	20.6	40	15	175	6	5	1.12	7

CAD INFO



SLEEVE



Green Pin Tycan® Sleeve

Sleeve made from Dyneema®

- **Material:** 100% Dyneema
- **Certification:** 2.1
- **Article code:** scan QR code to see article codes




for chain size	length	diameter	thickness	weight each
mm	a mm	b mm	c mm	kg
15x25	500	60	1	0.04
13x30	500	65	1	0.06
15x40	500	75	1	0.10

INFO





UCRCT



Green Pin Tycan® Grab Hook CL GR10

Grade 10 clevis grab hook

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL and MBL equals 2 x Lashing Capacity
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC[®] MPI[®] CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** GPUCRCT25 and GPUCRCT30 can also be directly connected with Green Pin Tycan® loadbinder (P-7180)

Scan for additional product details




for chain size	lashing capacity	length	width	width outside	opening	thickness	width	width outside	length outside	diameter pin	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
15x25	10	102	24	68	25	16	40	99	178	20	2.12
13x30	13.6	100	32	74	30	20	40	102	177	20	1.94
15x40	20.6	128	42	96	40	24	44.7	127	216.5	24	3.37

CAD INFO



UCSCT



Green Pin Tycan® Sling Hook CL GR10


Grade 10 clevis sling hook

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC[®] MPI[®] CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** GPUCRCT25 and GPUCRCT30 can also be directly connected with Green Pin Tycan® loadbinder (P-7180)




for chain size	lashing capacity	length	width	width opening	thickness	width	width outside	width outside	length outside	diameter pin	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
15x25	10	150	24	37	29	35	68	123	220	20	2.15
13x30	13.6	159	32	37	32	39	74	133	235	20	2.56
15x40	20.6	185	42	45	40	43	96	165	271	24	4.25

CAD INFO



P-7180



Green Pin TyCan® Ratchet Loadbinder GR10

Grade 10 ratchet type loadbinder


- **Material:** drop forged, grade 10
- **Safety factor:** MBL equals 2x Lashing Capacity
- **Standard:** EN 12195-3
- **Finish:** painted blue
- **Certification:** 2.1 2.2
- **Article code:** scan QR code to see article codes
- **Note:** Stf = 3000daN
UCRCT or UMJT are necessary to connect the loadbinder with the Green Pin TyCan® chain

Scan for additional product details





chain size	length handle	diameter	thickness	length barrel	length open position	length closed position	diameter eye inside	diameter eye outside	take-up	lashing capacity	proof load	minimum breaking load	weight each
mm	a	b	c	d	e	f	g	h	mm	t	t	t	kg
15x25	387	65	15	410	858	558	30	64	300	16	20	32	5.17
13x30	387	65	15	410	858	558	30	64	300	16	20	32	5.17

CAD



P-7170



Green Pin® Ratchet Loadbinder HK EN 12195-3

Ratchet type loadbinder with hooks according to EN 12195-3



- **Material:** drop forged, grade 8
- **Safety factor:** MBL equals 2 x Lashing Capacity
- **Standard:** EN 12195-3
- **Finish:** painted red
- **Certification:** 2.1 2.2
- **Article code:** scan QR code to see article codes
- **Note:** Stf = 3000 daN



chain size	length handle	diameter	thickness	length barrel	length open position	length closed position	width	take-up	lashing capacity	proof load	minimum breaking load	weight each
mm	a	b	c	d	e	f	g	mm	t	t	t	kg
8	387	65	15	255	735	575	11	160	4	5	8	4.86
10	387	65	15	255	760	595	13	165	6.3	7.9	12.6	5.12
13	387	65	15	260	840	690	16	150	10	12.5	21.2	7.65
16	387	65	15	260	840	690	19	150	16	20	32.2	9.68



P-7190



Green Pin® Ratchet Loadbinder EN 12195-3


Ratchet type loadbinder without hooks according to EN 12195-3

- **Material:** drop forged, grade 8
- **Safety factor:** MBL equals 2 x Lashing Capacity
- **Standard:** EN 12195-3
- **Finish:** painted red
- **Certification:** 21 22
- **Article code:** scan QR code to see article codes
- **Note:** Stf = 3000 daN


Scan for additional product details



chain size	length handle	diameter	thickness	length barrel	length open position	length closed position	diameter eye inside	diameter eye outside	take-up	lashing capacity	proof load	minimum breaking load	weight each
mm	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	mm	t	t	t	kg
8	387	65	15	255	534	374	18	50	160	4	5	8	3.31
10	387	65	15	255	543	379	20	55	164	6.3	7.9	12.6	3.51
13	387	65	15	260	564	414	26	66	150	10	12.5	21.2	3.96
16	387	65	15	260	564	420	30	71	144	16	20	32.2	4.11



P-7130



Green Pin® Ratchet Loadbinder HK

Ratchet type loadbinder with hooks

- **Material:** drop forged/cast steel
- **Safety factor:** MBL equals 3.5 x Lashing Capacity
- **Finish:** painted red or green
- **Certification:** 21 22
- **Article code:** scan QR code to see article codes



chain size	length handle	diameter	thickness	length barrel	length open position	length closed position	width	take-up	lashing capacity	proof load	minimum breaking load	weight each
mm	a mm	b mm	c mm	d mm	e mm	f mm	g mm	mm	t	t	t	kg
8 - 10	385	65	15	255	735	575	12	160	2.45	4.9	8.62	4.82
10 - 13	385	65	15	255	760	595	16	165	4.17	8.35	14.97	5.81
13 - 16	385	65	15	260	840	690	18	150	5.9	11.8	20.86	7.05





Green Pin® Ratchet Loadbinder

Ratchet type loadbinder without hooks

- **Material:** drop forged/cast steel
- **Safety factor:** MBL equals 3.5 x Lashing Capacity
- **Finish:** painted red or green
- **Certification:** 2.1 2.2
- **Article code:** scan QR code to see article codes



P-7150



chain size	length handle	diameter	thickness	length barrel	length open position	length closed position	diameter eye inside	diameter eye outside	take-up	lashing capacity	proof load	minimum breaking load	weight each
mm	a	b	c	d	e	f	g	h	mm	t	t	t	kg
8 - 10	385	65	15	255	534	374	18	50	160	2.45	4.9	8.62	3.27
10 - 13	385	65	15	255	543	379	20	55	164	4.17	8.35	14.97	3.45
13 - 16	385	65	15	260	564	412	26	66	152	5.9	11.8	20.86	3.84





Green Pin® Lever Loadbinder HK

Lever type loadbinder with hooks

- **Material:** drop forged/cast steel
- **Safety factor:** MBL equals 3.5 x Lashing Capacity
- **Finish:** painted green
- **Certification:** 2.1 2.2
- **Article code:** scan QR code to see article codes



P-7110




chain size	length	length open position	length closed position	length handle	length	length	width	take-up	lashing capacity	proof load	minimum breaking load	weight each
mm	a	b	c	d	e	f	g	mm	t	t	t	kg
8 - 10	610	592	488	408	287	287	12	104	2.45	4.9	8.62	3.65
10 - 13	768	680	550	458	325	325	16	130	4.17	8.35	14.97	5.08

C



S



S-Hook


- **Material:** high tensile steel
- **Safety factor:** MBL equals 4 x LC
- **Finish:** painted red
- **Certification:** 2.1 2.2
- **Note:** not designed for lifting

lashing capacity	diameter	length	width	weight each
t	a mm	b mm	c mm	kg
0.2	10	80	30	0.11
0.3	13	100	40	0.24
0.5	16	130	50	0.47
0.75	18	160	60	0.80
1	20	180	65	1.02
1.2	22	200	70	1.40
1.5	24	220	80	1.95
2	32	260	90	3.50
3	36	320	100	5.16
4	40	360	115	7.48
5	45	400	130	10.8
6	51	450	150	16.2

C



SO



S Eye Hook

- **Material:** high tensile steel
- **Safety factor:** MBL equals 4 x LC
- **Finish:** painted red
- **Certification:** 2.1 2.2
- **Note:** not designed for lifting

lashing capacity	diameter	length	width	width inside	weight each
t	a mm	b mm	c mm	d mm	kg
0.2	10	80	30	16	0.11
0.3	13	100	40	21	0.25
0.5	16	130	50	25	0.48
0.75	18	160	60	34	0.76
1	20	180	65	44	1.07
1.2	22	200	70	40	1.40
1.5	24	220	80	40	1.79
2	32	260	90	50	3.80
3	36	320	100	52	5.35



C

Clevish lashing hook

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 2 x LC
- **Finish:** painted red
- **Certification:** 2.1 2.2
- **Note:** not designed for lifting



CAC



for chain diameter	lashing capacity	length	width	width	thickness	width	width outside	width outside	length outside	diameter pin	width outside	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
8	4	65	10	10	16	23	38	56	107	9	19	0.34
10	6.3	82	12	13	25	31	46	75	136	12	27	0.85
13	10	113	16	16	30	43	61	102	185	16	36	1.98
16	16	130	20	19	38	49	69	118	215	20	40	2.95
18/20	25	152	24	24	40	58	88	142	254	22	44	5.12